



Common Nomenclature	Circuit-Start	"D" Boss - Boss min (inches)	"D" Boss - Boss max (inches)	"E" Tube Dia. (inches / mm)	Wattage (W)	Voltage (V)	Current (A)	Base Type
F24T12/HO	Rapid Start	21.72	21.91	1.5" / 38mm	37.0	41	0.800	R17d RDC
F36T12/HO	Rapid Start	33.72	33.91	1.5" / 38mm	50.0	59	0.800	R17d RDC
F48T12/HO	Rapid Start	45.72	45.91	1.5" / 38mm	63.0	78	0.800	R17d RDC
F60T12/HO	Rapid Start	57.72	57.91	1.5" / 38mm	75.5	98	0.800	R17d RDC
F72T12/HO	Rapid Start	69.72	69.91	1.5" / 38mm	87.0	117	0.780	R17d RDC
F84T12/HO	Rapid Start	81.72	81.91	1.5" / 38mm	100.0	135	0.800	R17d RDC
F96T12/HO	Rapid Start	93.72	93.91	1.5" / 38mm	113.0	153	0.790	R17d RDC
F48T12/VHO	Rapid Start	45.72	45.91	1.5" / 38mm	116.0	84	1.500	R17d RDC
F72T12/VHO	Rapid Start	69.72	69.91	1.5" / 38mm	168.0	125	1.520	R17d RDC
F96T12/VHO	Rapid Start	93.72	93.91	1.5" / 38mm	215.0	163	1.500	R17d RDC

TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 .X INDICATES ±0.020 INCHES; .XX INDICATES ±0.010 INCHES;  
 .XXX INDICATES ±0.005 INCHES; ANGLES ±1°

THIS DOCUMENT OR DATA INCLUDES MATTER WHICH IS A TRADE  
 SECRET OF LCD LIGHTING, INC. OR PROPRIETARY AND CONFIDENTIAL  
 TO LCD LIGHTING, INC. AND SHALL NOT BE USED IN ANY MANNER  
 EXCEPT IN CONJUNCTION WITH LCD LIGHTING, INC. BUSINESS WITHOUT  
 THE PRIOR WRITTEN CONSENT OF LCD LIGHTING, INC.

REV.	REVISION / DESCRIPTION	DATE	APPD.

PROJECT	
TITLE FLUORESC	
SCALE NTS	DRAWN BY B.K.
DATE 12/3/10	CHECKED BY