



Common Nomenclature	Circuit-Start	"A" BF-BF max (inches)	"B" BF-EOP min (inches)	"B" BF-EOP max (inches)	"C" EOP-EOP max (inches)	"E" Tube Dia. (inches / mm)	Wattage (W)	Voltage (V)	Current (A)	Base Type	Nom. Length (Fixture)	Spec Ref.
F48T12/SL	Instant Start	45.30	45.42	45.65	46.00	1.5" / 38mm	39.0	100	0.425	Single Pin	48"	ANSI C78.3-1978
F72T12/SL	Instant Start	69.30	69.42	69.65	70.00	1.5" / 38mm	57.0	149	0.425	Single Pin	72"	ANSI C78.3-1978
F96T12/SL	Instant Start	93.30	93.42	93.65	94.00	1.5" / 38mm	75.0	197	0.425	Single Pin	96"	ANSI C78.3-1978

<p>TOLERANCES UNLESS OTHERWISE SPECIFIED: .X INDICATES ±0.020 INCHES; .XX INDICATES ±0.010 INCHES; .XXX INDICATES ±0.005 INCHES; ANGLES ±1°</p> <p>THIS DOCUMENT OR DATA INCLUDES MATTER WHICH IS A TRADE SECRET OF LCD LIGHTING, INC. OR PROPRIETARY AND CONFIDENTIAL TO LCD LIGHTING, INC. AND SHALL NOT BE USED IN ANY MANNER EXCEPT IN CONJUNCTION WITH LCD LIGHTING, INC. BUSINESS WITHOUT THE PRIOR WRITTEN CONSENT OF LCD LIGHTING, INC.</p>	REV.	REVISION / DESCRIPTION	DATE	APPD.	PROJECT	GENERAL LAMPS		
					TITLE	FLUORESCENT LAMP - T12 SL		
					SCALE	DRAWN BY	DRAWING NO.	REV.
					NTS	B.K.		
					DATE	CHECK'D	LCD GEN T12 SL	-
					12/3/10			