



Common Nomenclature	Circuit-Start	"A" BF-BF max (inches)	"B" BF-EOP min (inches)	"B" BF-EOP max (inches)	"C" EOP-EOP max (inches)	"E" Tube Dia. (inches / mm)	Wattage (W)	Voltage (V)	Current (A)	Base Type	Nom. Length (Fixture)	Spec Ref.
F42T6/SL	Instant Start	39.30	39.42	39.65	40.00	T6 (3/4", 19mm)	25.5	150	0.200	Single Pin	42"	ANSI C78.3-1978
F64T6/SL	Instant Start	61.30	61.42	61.65	62.00	T6 (3/4", 19mm)	38.5	233	0.200	Single Pin	64"	ANSI C78.3-1978

TOLERANCES UNLESS OTHERWISE SPECIFIED: .X INDICATES ±0.020 INCHES; .XX INDICATES ±0.010 INCHES; .XXX INDICATES ±0.005 INCHES; ANGLES ±1°	REV.	REVISION / DESCRIPTION	DATE	APPD.	PROJECT	GENERAL LAMPS		
					TITLE	FLUORESCENT LAMP - T6 SL		
					SCALE	DRAWN BY	DRAWING NO.	REV.
	THIS DOCUMENT OR DATA INCLUDES MATTER WHICH IS A TRADE SECRET OF LCD LIGHTING, INC. OR PROPRIETARY AND CONFIDENTIAL TO LCD LIGHTING, INC. AND SHALL NOT BE USED IN ANY MANNER EXCEPT IN CONJUNCTION WITH LCD LIGHTING, INC. BUSINESS WITHOUT THE PRIOR WRITTEN CONSENT OF LCD LIGHTING, INC.					NTS	B.K.	LCD GEN T6 SL
					DATE	CHECK'D		
					12/3/10			